

Available from Master

11 Loton Avenue MIDLAND WA 6056 Ph: (08) 9274 7000 Fax: (08) 9250 4422

Email: sales@tankmaster.com.au

APPLICATION

Highly visible water level indicator for large water tanks and reservoirs

FEATURES & BENEFITS

- Designed to withstand the hardest weather conditions
- Innovative Uni-Ball joint suits all roof angles, on all tank types
- Made from the highest quality UV resistant materials
- Doesn't get stuck
- · Visible from a long distance

SPECIFICATIONS

- Stainless steel tube 2m (6.5ft)
- Maximum wind speed @ 2m (6.5ft): 120km/hr (75mph)
- Maximum wind speed @ 3m (10ft): 80km/hr (50mph), two 150mm (6") floats needed for 3m (10ft) height

AVAILABLE SIZES

- VisiBall
- 150mm (6") Ball Float (bottom float[s])
- 115mm (4") Ball Float (top float)

SPARES & ACCESSORIES

 VisiBall Extension Tube - 1m (3ft), comes with Twin Float Connector and female socket. Additional 150mm (6") float required, sold separately.

INSTALLATION

- Easy fit with only one 25mm (1") hole to be drilled
- Tube must be vertical
- Two 150mm (6") floats are required when the extension tube is used
- Maximum height: 3m (10ft)

PATENTS

- New Zealand Pat. No. NZ569558B
- Australian Pat. No. AU2008207462B2
- South African Pat. No. ZA200807409B







